SPLENDOR WAX

DESCRIZIONE

IL MIGLIOR RAPPORTO QUALITA' PREZZO

Cera per impianti a media velocità.
Cera di asciugatura lucidante a media concentrazione. Idonea in impianti con asciugatura vicina all'arco di ceratura. Lascia un effetto brillante immediatamente visibile.

- Buon potere lucidante e di asciugatura
- Non unge
- Veloce rottura dell'acqua

CARATTERISTICHE CHIMICO-FISICHE

PARAMETRI	VALORI
Aspetto fisico	Liquido limpido verde
Odore	Caratteristico
pH	6,3 ± 0,5
pH 1%	7,0 ± 0,5

APPLICAZIONE E DOSAGGIO

Impianti automatici: Far aspirare il prodotto puro dalla pompa dosatrice come da tabella.

Tipo di acqua	AUTOLAVAGGIO	
	ml per auto	
	Estate	Inverno
Dura (> 25°F)	30	40
Media (15 - 25 °F)	20	30
Dolce (5 - 15 °F)	7	12

SPLENDOR WAX

DESCRIPTION

EXCELLENT VALUE FOR MONEY

Drying wax for mid-speed car washing system. Medium concentrated drying wax. It is used in washing systems where the wax application arch is close to the drying. Leaves an immediately visible shining effect.

- Great polishing and drying action
- Does not leave smear marks
- Breaks water faster

PHYSICAL – CHEMICAL PARAMETERS

PARAMETERS	VALUES
Physical aspect	Limpid liquid, green
Odour	Peculiar
pH	6,3 ± 0,5
pH 1%	7,0 ± 0,5

APPLICATION

Automatic systems: Aspire the pure product from the dosing pump as per table.

Type of water	CAR WASH	
	ml per car	
	Summer	Winter
Hard (> 25°F)	30	40
Medium (15 - 25 °F)	20	30
Sweet (5 - 15 °F)	7	12

Frescura Sas di Andrea Frescura & C. - Via della Meccanica 15 36016 Thiene - Vicenza - Italy – www.frescurachem.com

Ed. 1 del 19/10/2020 Rev. 0 del 19/10/2020

Tipo di acqua	PISTE	
	ml per auto	%
Dura (> 25°F)	30	0,3
Media (15 - 25 °F)	20	0,2
Dolce (5 - 15 °F)	10	0,1

Type of water	BAYS	
	ml per car	%
Hard (> 25°F)	30	0,3
Medium (15 - 25 °F)	20	0,2
Sweet (5 - 15 °F)	10	0,1

AVVERTENZE

In caso di diluizione, non superare il rapporto di 1:4 e riproporzionare di conseguenza la quantità aspirata.
N.B: se si eccede nel dosaggio si possono verificare (soprattutto in presenza di acque dure) fenomeni di asciugatura insoddisfacente, formazione di puntinature bianche sulla carrozzeria ed annerimento delle spazzole. Nel periodo invernale si consiglia di non tenere a lungo all'esterno il prodotto diluito in quanto a temperatura inferiore a 2-3 °C può assumere un aspetto lattiginoso e separare.

CONTIENE TENSIOATTIVI CONFORMI AL REG. 648/2004/CE

WARNINGS

In the case of dilution do not exceed the ratio of 1 to 4 and hence the amount drawn to scale. NB: If you exceed the dose may occur (especially in hard water) unsatisfactory drying phenomena, the formation of white dots on its body and darkening of the brushes. In winter you should not keep long outside the diluted product when the temperature is below 2-3 °C; at these temperatures the product can have a milky appearance and separate.

CONTAINS SURFACTANTS ACCORDING TO REG. 648/2004/CE

Frescura Sas di Andrea Frescura & C. - Via della Meccanica 15 36016 Thiene - Vicenza - Italy – www.frescurachem.com

Ed. 1 del 19/10/2020 Rev. 0 del 19/10/2020